

TRANS DRIVE ATF DEXRON-II



Description

BENZOL® Trans Drive ATF Dexron-II is a high-performance automatic transmission oil, formulated with high quality hydro-treated base stocks and advanced additive system including viscosity index improvers, antioxidants, and defoamers providing smooth and controlled friction/wear characteristics.



Applications

BENZOL® Trans Drive ATF is particularly suitable for use in automatic transmissions of car & light trucks and On-highway & Off-highway heavy duty automatic transmissions.

Specifications and Approvals

MAN 339 Z1/V1/L2, MB-Approval 236.6, Voith H55.6335, GM Dexron IID

Technical Specifications

Performance Benefits

- An extremely high thermal load.
- A very shear stable viscosity-temperature behavior.
- Good oxidation and thermal stability reduces deposit formation.
- Compatible with all common seal materials.
- Reliable protection against wear, sludge, adhesion and Corrosion.

Product/Part Number

TD03010331	4 x 5	TD03010321	4 x 4
TD03010171	12 x 1	TD03010171	24 X 1
TD03010511	1 x 20	TD03010531	1 x 25
TD03010561	1 x 200	TD03010571	1 x 208
TD03010601	1x1000		

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Red
Density @ 15 °C, kg/L	D-1298	0.8555
Viscosity @ 100 °C, cSt	D-445	7.05
Viscosity @ 40 °C, cSt	D-445	39.80
Viscosity index	D-2270	140
Flash Point, °C (COC)	D-92	220
Pour Point, °C	D-97	-42
Foam SEQ.I/II/III	D-892	0/0/0
Brookfield viscosity@-40°C, cP	D-2983	30000

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

