

2T SUPER MARINE SAE 30 API TC-W3



Description

BENZOL® 2T Super Marine Outboard Oil SAE 30 API TC-W3 is a superior quality two-stroke lubricant specifically designed for water-cooled, high-revving engines with pre-mix or injection systems. Premium base stocks are blended with a modern ashless detergent additive package to provide fortification for maximum performance in outboard engines.



Applications

BENZOL® 2T Super Marine Outboard is designed for water-cooled two-stroke engines used in outboard marine applications. Mixing with the fuel should be in accordance with the manufacturer's recommendations.

Specifications and Approvals

API TC, NMMA TC-W3.

Technical Specifications

Tests	Method	Results
Appearance	Visual	Clear & Bright
Water	Hot Plate	Nil
Color	D-1500	Green/Blue
Density @ 15 °C, kg/L	D-1298	0.8780
Viscosity @ 100 °C, cSt	D-445	11.50
Viscosity @ 40 °C, cSt	D-445	79.75
Viscosity index	D-2270	136
Flash Point, °C (COC)	D-92	204
Pour Point, °C	D-97	-36
Foam SEQ.I/II/III	D-892	0/0/0
TBN, mg KOH/g	D-2896	4.5
Sulphated Ash, %	D-874	<0.005

Performance Benefits

- Prolongs engine life.
- Enhances engine performance.
- Minimizes wear, combustion chamber deposits, ring sticking, Piston burning.
- High anti-wear capacity.
- Reduced Maintenance Costs.
- Approved for use with most ethanol blended fuels.
- Outstanding results in reducing visible smoke and particle emissions.

Product/Part Number

OF18030331	4 x 5	OF18030321	4 x 4
OF18030171	12 x 1	OF18030171	24 x 1
OF18030511	1 x 20	OF18030531	1 x 25
OF18030561	1 x 200	OF18030571	1 x 208
OF18030601	1x1000		

HEALTH AND SAFETY

This product is not expected to have adverse health implications when used for its intended application. For detailed information on safe handling of this product, refer to its Material Safety Data Sheet (MSDS). To obtain an MSDS on this or any other BENZOL products, please visit www.benzollubricants.de

